

applicant re-writes the claim 7, according to the official action dated 08/10/2005, the claim 7 is only allowable portion of the instant invention, it should be incorporated with the claim 1 in a reasonable way, the applicant now is realized that a conduction unit buckling ring to conduct the electricity no matter with the metal cap and the spring. As the Supervisory Examiner kindly concerned the conduction function, the applicant deletes the words about metal cap and the spring either in claim 1 or claim 7, that is, in this instant invention, claims the conduction unit as a buckling ring only.

The new claims 13 as the other new independent claims remain the features of the claim 6 (also removes the metal cap and the spring) added with the limit of the amended claim 7, new claims 9,10, 11, and 12 remain the features of the original claims 2,3,4 and 5 dependent on the amended claim 7. Claim 8 is not compatible with the amended Claim 7, so it should be cancelled.

AMENDMENT

IN THE CLAIM

Please cancel the claims 1 to 6 and 8, without prejudice or disclaimer of the subject matter thereof, and add new claims 9-13, where the dependent claim preamble 'The touch controlled lighting device as claim 1 claimed' and limit "having the function of spring

and metal cap” are deleted from the original claim 7, and then incorporated with the limit of the claim 1, because the conduction unit buckling ring is only allowable, so the limit of claim 1 “a spring enclosing an periphery of the battery set and a length of the spring being larger than an expandable spring of the battery set; a metal cap in a lower end of the spring and distanced from the spring with a predetermined distance” are not suitable to add to the original claim 7 to form an independent claim 7. The same words should be deleted from the original claim 6, which is not suitable to add to the new claim 13. Therefore, the claim 7 is incorporated with the claim 1 no mention about metal cap and spring as a new independent claim of the present invention. The new claims 9,10,11,and 12 add features of the original claims 2,3,4, and 5 dependent on the amended claim 7. The new claim 13 is the other new independent claim adds the feature of the original claims 6 incorporated with the amended claim 7. Thereby, it is assured that the new claims 9, 10, 11and 12 are based on the original claims and thus no new matter is added. The relation of the new claims with respect to the original claims are illustrated in the following REMARK from which Examiner can know the relation easily.

List of Claims

Claim 1-6 (cancelled)

Claim 7 (amended) A touch controlled lighting emitting device comprising: a base having a device groove at an upper end thereof and a hollow battery set at an lower end thereof; a light emitting body installed on the device groove having a long lead and a short lead; a battery set installed in the battery groove ; wherein ~~The touch controlled lighting emitting device as claimed in claim 1, further comprising a conduction unit having the function of spring and metal cap, ,~~ a top of the conduction unit having a buckling ring; a lower edge of the buckling ring extends with an L shape guide sheet; a horizontal section of the guide sheet having a convex portion, and the convex portion of the horizontal section being retained with a predetermined distance to the electrode, a bottom of the device groove of the base is formed with at least one through hole which is communicated with the battery groove; a wall of the device groove is formed with at least one axial slot; a wall of the battery groove is formed with at least one axial recess; each slot is communicated with a respect recess; the short lead of the light emitting body passes through the through hole to be in contact with a top electrode of the battery set in the battery groove; the long lead extends through one slot of the device groove and then bends downwards to be in contact with the convex portion of the L shape guide sheet of the lower edge of the buckling ring, further, the wall of the battery groove are

formed with two notches; a lower inner wall of the battery groove is formed with a ring .

Claim 8 (cancelled)

Claim 9 (new) The touch controlled lighting emitting device as claimed in claim 7, wherein there are two through holes at the bottom of the device groove; and there are two slots and two recesses which are arranged at opposite sides of the walls of the device groove and battery groove, respectively, the two through holes, two slots, two recesses are at the same diameter line of the bottom of the device groove.

Claim 10 (new) The touch controlled lighting emitting device as claimed in claim 7, wherein the two through holes are in a radial recess at the bottom of the device groove; the long lead is embedded in the radial recess.

Claim 11 (new) The touch controlled lighting emitting device as claimed in claim 7, wherein the light emitting body includes an IC board and an IC, and light emitting elements.

Claim 12 (new) The touch controlled lighting emitting device as claimed in claim 7, wherein at least one sound emitting element is in the device groove.

Claim 13 (new) A touch controlled lighting emitting device comprising: a base having a device groove at an upper end thereof and a hollow battery set at an lower end thereof; a sound emitting body installed on the device groove having a long lead and a short lead; a battery set installed in the battery groove;

wherein a top of the conduction unit having a buckling ring; a lower edge of the buckling ring extends with an L shape guide sheet; a horizontal section of the guide sheet having a convex portion, and the convex portion of the horizontal section being retained with a predetermined distance to the electrode, a bottom of the device groove of the base is formed with at least one through hole which is communicated with the battery groove; a wall of the device groove is formed with at least one axial slot; a wall of the battery groove is formed with at least one axial recess; each slot is communicated with a respect recess; the short lead of the light emitting body passes through the through holes to be in contact with a top electrode of the battery set in the battery groove; the long lead extends through one slot of the device groove and then bends downwards to be in contact with the convex portion of the L shape guide sheet of the lower edge of the buckling ring; further, the wall of the battery groove are formed with two notches; a lower inner wall of the battery groove is formed with a ring.